

SAFETY DATA SHEET

1. Identification		
Product identifier	Granusol Iron 50%	
Other means of identification	None.	
Recommended use	Not available.	
Recommended restrictions	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.	
Manufacturer/Importer/Supplier	/Distributor information	
Manufacturer		
Company name Address	Prince Minerals LLC 15311 Vantage Pkwy W Suite 350 Houston, TX 77032 United States	
Telephone	General Information	(713) 955-5398
Website	www.princecorp.com	
E-mail	Not available.	(000) (01 0000
Emergency phone number	CHEMTREC	(800) 424-9300
2. Hazard(s) identification		
Physical hazards	Not classified.	
Health hazards	Carcinogenicity	Category 1A
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	
Hazard statement	May cause cancer.	
Precautionary statement		
Prevention		ore use. Do not handle until all safety precautions have been read ve gloves/protective clothing/eye protection/face protection.
Response	If exposed or concerned: Get r	nedical advice/attention.
Storage	Store locked up.	
Disposal	Dispose of contents/container	in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Iron Sucrate- Complex Mixture of Iron Oxide and Sugar		N/A	65 - 80

Chemical name	Common name and synonyms	CAS number	%
CALCIUM SULFATE	CALCIUM SULPHATE, NATURAL GYPSUM	7778-18-9	3 - < 5
Other components below report	able levels		20 - < 30
mpurities			
Chemical name		CAS number	%
SILICA, CRYSTALLINE (QUAR		14808-60-7	< 1.53
Composition comments	Occupational Exposure Limits for constituents ar Limits for impurities are listed in Section 8.	re listed in Section 8. Occ	upational Exposure
4. First-aid measures			
nhalation	Move to fresh air. Call a physician if symptoms d	levelop or persist.	
Skin contact	Wash off with soap and water. Get medical atten	tion if irritation develops	and persists.
Eye contact	Do not rub eyes. Rinse with water. Get medical a	attention if irritation develo	ops and persists.
ngestion	Rinse mouth. Get medical attention if symptoms	occur.	
Aost important	Dusts may irritate the respiratory tract, skin and	eyes.	
symptoms/effects, acute and lelayed			
ndication of immediate nedical attention and special reatment needed	Provide general supportive measures and treat s Symptoms may be delayed.	symptomatically. Keep vic	tim under observatio
General information	IF exposed or concerned: Get medical advice/att of the material(s) involved, and take precautions		cal personnel are av
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon	dioxide (CO2).	
Jnsuitable extinguishing nedia	Do not use water jet as an extinguisher, as this v	vill spread the fire.	
Specific hazards arising from he chemical	During fire, gases hazardous to health may be for	ormed.	
Special protective equipment and precautions for firefighters	Material can be slippery when wet.		
Fire fighting equipment/instructions	Use water spray to cool unopened containers.		
Specific methods	Use standard firefighting procedures and conside	er the hazards of other in	volved materials.
General fire hazards	No unusual fire or explosion hazards noted.		
6. Accidental release meas	sures		
	Keep unnecessary personnel away. Keep people	a away from and upwind	of spill/look Mataria
Personal precautions, protective equipment and emergency procedures	be slippery when wet. Wear appropriate protective NIOSH/MSHA approved respirator if there is a rist the exposure limits. Ensure adequate ventilation spillages cannot be contained. For personal prot	ve equipment and clothin sk of exposure to dust/fur . Local authorities should ection, see section 8 of th	g during clean-up. U me at levels exceedi be advised if signific me SDS.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Co HEPA filter.	ollect dust using a vacuur	n cleaner equipped
	Large Spills: Wet down with water and dike for la container. Avoid the generation of dusts during c with water.		
	Small Spills: Sweep up or vacuum up spillage ar waste disposal, see section 13 of the SDS.	nd collect in suitable conta	ainer for disposal. Fo

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

	Туре	Value	Form
CALCIUM SULFATE (CAS 7778-18-9)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFI Impurities	R 1910.1000) Type	Value	Form
SILICA, CRYSTALLINE (QUARTZ) (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit			_
Components	Туре	Value	Form
CALCIUM SULFATE (CAS 7778-18-9)	TWA	10 mg/m3	Inhalable fraction.
Impurities	Туре	Value	Form
SILICA, CRYSTALLINE (QUARTZ) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
CALCIUM SULFATE (CAS 7778-18-9)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Impurities	Туре	Value	Form
SILICA, CRYSTALLINE (QUARTZ) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
logical limit values	No biological exposure limits noted f	or the incredient(s)	
logical mint values	No biological exposure limits hoted i		
propriate engineering trols	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to mair exposure limits have not been establ engineering measures are not suffici Occupational Exposure Limit (OEL), ground, cut, or used in any operation ventilation to keep exposures below	D air changes per hour) should b applicable, use process enclosur ntain airborne levels below recon lished, maintain airborne levels t ient to maintain concentrations o suitable respiratory protection m o which may generate dusts, use	es, local exhaust ventilation mended exposure limits. o an acceptable level. If f dust particulates below th sust be worn. If material is appropriate local exhaust
vidual protection measures,	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been establ engineering measures are not suffici Occupational Exposure Limit (OEL), ground, cut, or used in any operation ventilation to keep exposures below such as personal protective equipm	D air changes per hour) should b applicable, use process enclosur ntain airborne levels below recon lished, maintain airborne levels t ient to maintain concentrations o suitable respiratory protection m which may generate dusts, use the recommended exposure limi nent	es, local exhaust ventilation mended exposure limits. o an acceptable level. If f dust particulates below th sust be worn. If material is appropriate local exhaust
bropriate engineering trols	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to mair exposure limits have not been establ engineering measures are not suffici Occupational Exposure Limit (OEL), ground, cut, or used in any operation ventilation to keep exposures below	D air changes per hour) should b applicable, use process enclosur ntain airborne levels below recon lished, maintain airborne levels t ient to maintain concentrations o suitable respiratory protection m which may generate dusts, use the recommended exposure limi nent	es, local exhaust ventilation mended exposure limits. o an acceptable level. If f dust particulates below th sust be worn. If material is appropriate local exhaust
vidual protection measures,	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been establ engineering measures are not suffici Occupational Exposure Limit (OEL), ground, cut, or used in any operation ventilation to keep exposures below such as personal protective equipm	D air changes per hour) should b applicable, use process enclosur ntain airborne levels below recon lished, maintain airborne levels t ient to maintain concentrations o suitable respiratory protection m which may generate dusts, use the recommended exposure limit nent s (or goggles).	es, local exhaust ventilatio mmended exposure limits. o an acceptable level. If f dust particulates below th lust be worn. If material is appropriate local exhaust ts.
vidual protection measures, Eye/face protection Skin protection Hand protection	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to mair exposure limits have not been establ engineering measures are not suffici Occupational Exposure Limit (OEL), ground, cut, or used in any operatior ventilation to keep exposures below such as personal protective equipm Wear safety glasses with side shield For prolonged or repeated skin conta	D air changes per hour) should b applicable, use process enclosur ntain airborne levels below recon lished, maintain airborne levels t ient to maintain concentrations o suitable respiratory protection m which may generate dusts, use the recommended exposure limit nent s (or goggles).	es, local exhaust ventilatio mmended exposure limits. o an acceptable level. If f dust particulates below th lust be worn. If material is appropriate local exhaust ts.
vidual protection measures, Eye/face protection	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to mair exposure limits have not been establ engineering measures are not suffici Occupational Exposure Limit (OEL), ground, cut, or used in any operatior ventilation to keep exposures below such as personal protective equipm Wear safety glasses with side shield	D air changes per hour) should b applicable, use process enclosur ntain airborne levels below recon lished, maintain airborne levels t ient to maintain concentrations o suitable respiratory protection m which may generate dusts, use the recommended exposure limit nent s (or goggles).	es, local exhaust ventilation mended exposure limits. o an acceptable level. If f dust particulates below th sust be worn. If material is appropriate local exhaust ts.

Material name: Granusol Iron 50%

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

,	•
Appearance	Granular. Dry flowable granules.
Physical state	Solid.
Form	Powder.
Color	Black.
Odor	None.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	> 3002 °F (> 1650 °C)
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.00004 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	98.00 lb/ft3 estimated
Specific gravity	2.96 estimated
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Dust may irritate respiratory system. Prolonged inhalation may be harmful.
Skin contact	Dust or powder may irritate the skin.

Eye contact	Dust may irritate the eyes.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Dusts may irritate the respiratory tract, skin and eyes.
Information on toxicological effe	ects
Acute toxicity	Not available.
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	n
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk" (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.
IARC Monographs. Overall	Evaluation of Carcinogenicity
OSHA Specifically Regulate Not listed.	(QUARTZ) (CAS 14808-60-7) 1 Carcinogenic to humans. ad Substances (29 CFR 1910.1001-1050) bogram (NTP) Report on Carcinogens
	(QUARTZ) (CAS 14808-60-7) Known To Be Human Carcinogen.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.
12. Ecological information	
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.
13. Disposal consideration	ns
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous wasto codo	Not regulated

Hazardous waste codeNot regulated.Waste from residues / unused
productsDispose of in accordance with local regulations. Empty containers or liners may retain some
product residues. This material and its container must be disposed of in a safe manner (see:
Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US** federal regulations Standard, 29 CFR 1910.1200. One or more components are not listed on TSCA. TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4) Not listed. SARA 304 Emergency release notification Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed. Superfund Amendments and Reauthorization Act of 1986 (SARA) Immediate Hazard - No **Hazard categories Delayed Hazard - Yes** Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No SARA 302 Extremely hazardous substance Not listed. SARA 311/312 Hazardous No chemical SARA 313 (TRI reporting) Not regulated. Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated. Safe Drinking Water Act Not regulated. (SDWA) **US state regulations** US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a)) SILICA, CRYSTALLINE (QUARTZ) (CAS 14808-60-7) **US. Massachusetts RTK - Substance List** CALCIUM SULFATE (CAS 7778-18-9) SILICA, CRYSTALLINE (QUARTZ) (CAS 14808-60-7) US. New Jersey Worker and Community Right-to-Know Act CALCIUM SULFATE (CAS 7778-18-9) SILICA, CRYSTALLINE (QUARTZ) (CAS 14808-60-7) Material name: Granusol Iron 50% 1070 Version #: 07 Revision date: 08-17-2015 Issue date: 12-18-2014

US. Pennsylvania Worker and Community Right-to-Know Law

CALCIUM SULFATE (CAS 7778-18-9) SILICA, CRYSTALLINE (QUARTZ) (CAS 14808-60-7)

US. Rhode Island RTK Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

SILICA, CRYSTALLINE (QUARTZ) (CAS	Listed: October 1, 1988
14808-60-7)	

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date Revision date Version #	12-18-2014 08-17-2015 07
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	Composition / Information on Ingredients: Disclosure Overrides Exposure Controls / Personal Protection: OELs